



Antiquax Ring Remover

Waterloo Road, London NW2 7TX Telephone: +44(0)20 8450 4666

CODE ANTQRINGR200

Туре	A mixture of fine abrasives dispersed in special water based lubricating medium.
Intended Use	Removal of water and heat mark damage from a range of polished surfaces such as lacquers, varnishes and French polish.
Special Features	Low odour. Will not destroy attractive patina that has been acquired due to ageing.
Preparation	The surface must be clean, smooth, dry and free from wax, dust and contaminants. SHAKE WELL BEFORE USE
Application	Pour the Ring Remover onto a lint free cloth and rub with pressure over the mark in the direction of the grain until the mark is removed. If the mark does not disappear apply more Ring Remover to the cloth and continue rubbing until the mark is removed. Buff with a clean cloth and then wax if required. For deeper marks the Ring remover can be applied with Rustins Fine Steel Wool (grade0000). For satin or matt finishes the same grade of steel wool may be used to matt the surface down after the Ring Remover has been used as it may produce a shiny surface.
Coats	One application is normally sufficient.
Drying Time	N/A
Re-coating Time	N/A
Application Temp.	Ideally 15-25°C.
Coverage	N/A
Maintenance	Re-apply when necessary.
Compatibility	Compatible with most polished surfaces such as lacquers, varnishes and French polish. Not suitable for furniture which has not been varnished and is only wax finished.
Settlement	SHAKE WELL BEFORE USE
Shelf-life/Storage	Many years if stored in original, tightly closed container in normal conditions. Protect from frost.
Hazards	Non-flammable. Flash point: Nil. Avoid contact with eyes, skin and clothing. Wash hands after use and dry them. A Full Safety Data Sheet is available upon request or on www.antiquax.co.uk
Clean-Up	Hands and application cloths can be cleaned in warm soapy water.
Sizes	200 ml



Waterloo Road, London NW2 7TX Telephone: +44(0)20 8450 4666

TECHNICAL DATA SHEET

Antiquax Ring Remover

CODE ANTQRINGR200